


## Luer Lock Tubing Connector




Male Luer Lock connector with rotating sleeve,  
fits 3x4.1 mm tubing.  
Assembled automatically in Clean Room.

**Art. No.**                      Flow rate              410 ml/min  
**964411**                      Residual vol.        0,1 ml  
   Drawing                  512

<i>elements</i>	<i>material</i>
Body	ABS transparent
Rotating	ABS White
sterilize	EtO

PACKAGING: No. 10,000 pcs. in bulk  
cm 30x42x30 - kg 10.9  
inch 11.8x16.5x11.8 – lb 24.0  
Vol. 0.037 m<sup>3</sup>

## Luer Lock Tubing Connector with Hydrophobic Filter



Male Luer Lock connector with rotating sleeve  
and hydrophobic filter cap pore size 0.8 µm,  
fits 3x4.1 mm tubing.  
Assembled automatically in Clean Room.

**Art. No.**                      Flow rate              410 ml/min  
**964911**                      Residual vol.        0,1 ml  
   Drawing                  511

<i>elements</i>	<i>material</i>
Body	ABS transparent
Rotating	ABS White
Cap	HDPE
sterilize	EtO

PACKAGING: No. 7,000 pcs. in bulk  
cm 30x42x30 - kg 12.14  
inch 11.8x16.5x11.8 - lb 26.76  
Vol. 0.037 m<sup>3</sup>